

PASSENGER & MATERIAL HOIST

MS-2035

LIFTEC

Technical Data

MODEL		MS-2035-45	MS-2035-60
Capacity	Pay Load	2.0 Ton	2.0 Ton
	Max. Speed	45 M/min	60 M/min
	Max. Lifting Height	200 ~ 300 M	200 ~ 300 M
Electrical Data	Motor	15Kw x 2	22Kw x 2
	Brake	DC 190 V	DC 190 V
	MCCB	100 A	100 A
	KVA	45 KVA	60 KVA
	Power supply	380V. 50/60Hz	380V. 50/60Hz
Size	Cage(W x L x H)	1.3M x 3.5M x 2.2M	1.3M x 3.5M x 2.2M
	Mast(W x L x H)	0.65M x 0.65M x 1.5M	0.65M x 0.65M x 1.5M
Driving Method		Rack & Pinion	Rack & Pinion
Safety Device Type		LSD 45	LSD 60
Running Control		Frequency (45Kw)	Frequency (45Kw)
Tie in Interval		10.5 M	10.5 M



We lift the World

Passion for innovation
New Way Forward
Optimum Solutions

TEL : +82 - 31 - 322 - 3000 FAX : +82 - 31 - 322 - 3010
Website : www.liftec.co.kr E-mail : sales@liftec.co.kr