

MSHD-10N (DSTAVD110X/XAA)

1x10 D-TV Distributor

IMAGE



DEFINITION

- MSHD-10N distribute received one(1) D-TV(Y,Pb,Pr) and audio(R,L) signal to the ten(10) channels.
- It is recommended reliable test room and show room.

SPECIFICATION

| | |
|--------------------------|---|
| Input/Output Channel | 1 Channel / 10 Channels |
| Pixel Clock | 8~150MHz |
| Input Connector | Video(Y,Pb,Pr) : RCA, Audio(R,L) : RCA |
| Output Connector | Video(Y,Pb,Pr) : RCA, Audio(R,L) : RCA |
| Y Level Attenuation | Input(1.0Vp-p / Load 75ohm) \pm 20mV : Level Control for VR |
| Pb, Pr Level Attenuation | Input(700mV / Load 75ohm) \pm 10mV : Level Control for VR |
| Audio Bandwidth | 20Hz~20KHz |
| Resolution | 480i/p, 576i/p, 720p, 1080i/p for ATSC and DVB Format |
| Power Consumption | AC 100~240VAC, 50/60Hz Auto Switch |
| Operating Conditions | * Temperature : 0~40°C * 80% Humidity, Non-condensing |
| Dimension(WXDXH) | 270 X 100 X 95mm, Weight : 1Kg |

* All specifications are subject to change without any notice.

Tel. 82-55-297-8880 / Fax. 82-55-256-7388

Address. #42-20, Palyong, Changwon, Gyeongnam, 641-847, Korea

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!