

MSHD-02

1x2 D-TV Distributor

IMAGE



DEFINITION

- BNC Connector로 입력되는 Component 신호를 감쇄 및 왜곡 없이 2개의 출력으로 분배하는 검사 라인용 정밀급 분배기 입니다.
- DTV (Component) Format의 최고 Clock 1920×1080P / 148.5MHz까지 지원하는 High Bandwidth Video Distributor IC를 사용 하였습니다.

SPECIFICATION

Input/Output Channel	1 Channel / 2 Channels
Pixel Clock	8~150MHz
Input Connector	Video(Y,Pb,Pr) : BNC
Output Connector	Video(Y,Pb,Pr) : BNC
Y Level Attenuation	Input(1.0Vp-p / Load 75ohm)±20mV : Level Control for VR
Pb, Pr Level Attenuation	Input(700mV / Load 75ohm)±10mV : Level Control for VR
Resolution	480i/p, 576i/p, 720p, 1080i/p for ATSC and DVB Format
Power Consumption	AC 100~240VAC, 50/60Hz Auto Switch
Operating Conditions	* Temperature : 0~40℃ * 80% Humidity, Non-condensing
Dimension(WXDXH)	245 X 140 X 40mm, Weight : 0.7Kg

* All specifications are subject to change without any notice.

전화. 055-297-8880 / 팩스. 055-256-7388

주소. 경남 창원시 팔용동 42-20번지 (우641-847)

Homepage. www.Ltdmaster.com

E-mail. sales@Ltdmaster.com / webmaster@Ltdmaster.com

Master Co., Ltd



Find Your Digital Solutions!