

MPCU-1600

Remote Power Control Unit



장비개요 및 성능

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

Description

- 본 장비는 Remote Power Controller로 여러 곳이나 한 자리에 다수로 설치 된 Monitor (기타 전원 공급 장치)의 Power를 Remote로 ON/OFF 할 수 있는 장비이다.

Features

- 기능은 Remote 제어시 개별 제어 및 All 제어 기능이 있으며 주변 기기와 I/F하여 운영 S/W로도 제어가 가능하다.
- 장비의 Front에 제어용 Switch가 부착되었으며 S/W에 의한 제어와 통신제어가 가능하도록 통신 Port를 내장하고 있다.

Panel Drawing



Specifications

- General Part
 - CPU : One Chip 8 Bit Micro Processor 89C52
 - Memory : 93C66
 - Communication serial asynchronous : RS-232C 9600BPS, N, 8, 1
 - Output port : 16 channel
 - Output power : AC 220V 10A
 - Control method : manual, program control
 - Control shape : one on/off, all on/off
 - Correspondent ports enable to control operating software : RS-232C

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

**Asia
China
Singapore
Korea**

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217

MPCU-1600

Remote Power Control Unit



장비개요 및 성능

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

■ Specifications

○ Case & Power Part

- Power source : AC 85 ~ 240V 50 ~ 60Hz
- Temperature : 0°C ~ 40°C
- Power consumption : Below 30Watt
- Type : 19" Rack Type
- Dimensions : 483(W) * 89(H) * 300(D) mm

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech. All rights reserved
Lead the 21st century with technology and service ..

Asia
China
Singapore
Korea

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217