

Description

- 19" Touch Panel is designed to work with Control PC, Main Control Unit (MMCU-100S, 150S, 200S, 150S, 300S etc.).

Features

- LCD Touch Panel Monitor is connected to PC by USB port, used without keyboard/mouse and it takes five-ultrasonic cables.

Panel Drawing



Specifications

- General Part
 - Case/bezel color : Dark gray
 - Display Size : 19형 diagonal
 - Useful screen area : Horizontal: 14.82" (376.32 mm), Vertical: 11.85" (301.06 mm)
 - Monitor dimensions : Width: 16.9" (429 mm), Height : 15.21" (386 mm), Depth : 8.15" (207 mm)
 - Resolution : 1280 x 1024
 - Colors : 16.2 million with dithering
 - Brightness LCD panel : 270 cd/m2
 - Touchscreen : IntelliTouch (five-ultrasonic cables), Touch Interface : Dual (Serial/USB)
 - Response time : 8m sec (typical)
 - Viewing angle(typical, from center) : Horizontal (left/right): $\pm 70^\circ$ or 140° total, Vertical (up/down): $75^\circ/60^\circ$ or 135° total
 - Contrast ratio : 550:1 (typical)
 - Input video format : RGB analog
 - Input sync format : Separate H & V sync, composite sync, sync-on-green
 - Input sync format : Separate H & V sync, composite sync, sync-on-green
 - Input video signal connector : Mini D-Sub 15-Pin VGA type
 - Input frequency : Horizontal: 31.5-80 kHz, Vertical: 56.3-75 Hz
 - Vesa mount : 100 mm
 - Agency approvals : UL/CUL, FCC, CE, TÜV-GS, VCCI, IC, C-Tick
- Power Part
 - Power source : AC100-240V , 50/60Hz