

Description

- 15" All-in-one Touch Computer Panel is designed to control integrating system with Main Control Unit (MMCU-100S, 150S, 200,250S, 300S) through RS-232C port.

Features

- Based on PC structure, its all purpose system is compatible with various CPU from NS Geode 233/300 MHz to Intel Pentium III 850MHz.
- Basically 4 Serial Port, 10/100 Ethernet, Sound, USB Port are installed. Additionally various I/O Card, PCMCIA Card, VISION Card are available for Field Bus Master Card, Motion Controller for more PC control usage.

Panel Drawing



Specifications

- General Part
 - Installing Copper Radiant Heat Panel and Dual Ball Bearing Cooling Fan prevent heat problem for CPU of Pentium III
 - One of the safest chipset in the field-Intel440bx is used for main CPU board.
 - Disconnecting external noise for serial ports protects ESD of 1.5Kv.
 - Advanced 10/100 Base Ethernet (Supports Wake on LAN, Boot Rom, PXE function))
 - Use best VGA Controller - C&T 69030
 - Enables LCD Luminous Intensity control.
 - Self Diagnosis Function- GENESYS GL518SM
 - Built-in Stereo Audio with 3watt GPS and Flash Disk support (No amplifier needed)
 - PCI and ISA
 - 3.5"Hdd, Slim Size CD-ROM, 3.5" Fdd
 - DISPLAY TYPE : 12.1" TFT
 - RESOLUTION : 800 * 600
 - MAX COLORS : 262K
 - Slot : 1 PCI or 1 ISA
 - CPU : Intel Celeron/Pentium III/850 Ns Ge Ode 233/266/300

MTS-15-3

Touch Panel



Equipment Overview & Function

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

■ Specifications

○ General Part

- MEMORY : 256MB SDRAM (EMB-370 BOARD)/128MB SDRAM (EMB-586G BOARD)
- TOUCH SCREEN : 3M Dynapro Touch Screen : (ANAIOG REGISTIVE TYPE)
- THERS : 4 Serial Port, 1 Parallel Port, Sound / Mic / Line In Ports, External Crt Port, 2 Usb Port, 10/100M Lan
- RELATIVE HUMIDITY : 5% ~ 85% / 40°C(Non-Condensing)
- VIBRATION (OPERATION) : 5 ~ 500Hz 1G Rms Random Vibration

○ FRONT PANEL

- 7 Layer Dynapro Touch Screen gives maximum confidence
- Tempered Acrylic Screen provides perfect protection
- Satisfied NEMA4/12IP65 standard

○ Power Part

- Power source : 80 Watts, Input Voltage 90 ~ 270VAC/47 ~ 63Hz, Output Voltage +5V/10A, +12V/2.0A,

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

Asia
China
Singapore
Korea

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217