

MMS-V64SERIES

Video Matrix Switcher



Equipment Overview & Function

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>


Description

- Video Matrix Switcher enables to receive 64 video signals and to distribute & route 64 video outputs. Additional Input/output Video Extension Shelf helps to maximize 1024 Input/64 Output.

Features

- Composition of Input/output Shelf makes maximum 1024x64 extensions.
- Input Shelf consists of Four 16 Channel Input Cards, Four 16 Channel Output Extension Cards, One CPU Card, and One Power Card.
- Output Shelf composed of 64 Video Output.
- Each output video level can be adjustable. There's Sync Input Port for smooth switching.
- Built-in RS-232C(422), Lan Port enables to control by remote as well as keyboard and control PRG.
- Built-in Control panel in front of the device enables easy operation without separated control panel.
- The front LCD panel enables easy view of inputs and outputs.
- LED provides view of transmission status with Remote Control and Memory Back-up Function helps to maintain the last status even if it is turned off.

Panel Drawing



[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech. All rights reserved
Lead the 21st century with technology and service ..

**Asia
China
Singapore
Korea**

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217

MMS-V64SERIES

Video Matrix Switcher



Equipment Overview & Function

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

■ Specifications

○ Video Part

- Input/Output number : 64 x 64 (Max 1024 x 64)
- Input/Output type : Composite video 1Vp-p, 75ohm
- Input/Output connector : BNC
- Sync : standards, BNC, 75ohm
- Extension connector : Ribbon cable connector
- S/N Ratio : below 80dB
- Crosstalk : below 67dB
- Frequency response : $\pm 0.1\text{dB}$ (750KHz ~ 4.7MHz)
- Differential phase : 0.1°
- Differential gain : 0.1%
- Bandwidth : 60 MHz (-3 dB), fully loaded

○ MMS-V64SERIES

- Input shelf : MMS-V64SERIES
- Extension shelf : MMS-V64EX
- Output shelf : MMS-V64VOM

○ Remote Control Part

- Serial control : 2 RS-232, d-sub 9pin connect
- Ethernet control(Option) : 1 RJ-45 female connector

○ Case & Power Part

- Power source : AC 85 ~ 240V 50 ~ 60Hz
- Temperature : 0°C ~ 40°C
- Power consumption : MMS-V64SERIES below 70W, MMS-V64EX below 70W, MMS-V64VOM below 30W
- Type : 19" Rack type
- Dimensions : MMS-V64SERIES 483(W) * 267(H) * 260(D)mm
MMS-V64EX 483(W) * 267(H) * 260(D)mm
MMS-V64VOM 483(W) * 133.5(H) * 210(D)mm

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech. All rights reserved
Lead the 21st century with technology and service ..

**Asia
China
Singapore
Korea**

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217