

MID-800

ID & Time Generator



Equipment Overview & Function

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

Description

- This is a versatile ID & Time Display Generator by receiving eight video signals.

Features

- Year, month, date, hour, minute and second are able to be displayed as well as Korean, English, and symbols.
- Outline of the letter/brightness control and letter/time blinking function are available.
- Background Pixels to Gray title appear even if Input Source Function has lost on LED.
- Supports various fonts from Window and it is can be downloaded from serial & USB.

Panel Drawing



Specifications

- Video Part
 - Video input : 8 port
 - Video output : 8 port
 - Input/Output impedance : NTSC composite video BNC 1Vp-p 75ohm
 - Bal level : 100 IRE
 - Sync level : 40 IRE
 - Differential phase : 0.5°
 - Differential gain : 0.5%

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech. All rights reserved
Lead the 21st century with technology and service ..

**Asia
China
Singapore
Korea**

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217

MID-800

ID & Time Generator



Equipment Overview & Function

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

■ Specifications

- Text Part
 - Korean (Max) : 30 (12x18=30,16x16,18x18=20,24x24=15,32x32=10)
 - English (Max) : 30(12x18=30,16x16,18x18=20, 24x24=15,32x32=10)
- Time Part
 - The Exact Time
 - Year, Month, Date, Hour, Minute, Second Symbols
- Case & Power Part
 - Power source : AC 85 ~ 220V, 50 ~ 60Hz
 - Temperature : 0°C ~ 40°C
 - Power consumption : below 30Watt
 - Type : 19" rack type
 - Dimensions : 483(W) * 44.5(H) * 300(D) mm

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

Asia
China
Singapore
Korea

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217