

Description

- Video Transmitter sends maximum 1000M Composite Video input by UTP (Unshielded Twisted Pair) Cable.

Features

- Video input supports NTSC/PAL. UTP Cable used CATEGORY 5, 5E, 6 types. Transmitter and receiver are needed to be connected point-to-point and signals controlled through UTP cable so it's not necessary to install extra cable.
- Supplied AC 12V power through UTP cable from MVUR-100, MVUT-100 allows extra adaptor for power supply. Camera Pan/Tilt control signal and unbalanced signal can be selected and transmitted from AUX terminal.

Panel Drawing



Specifications

- General Part
 - Input : 1 Vp-p Composite Video, 75Ω, NTSC/PAL, BNC Connector
 - Output : Balanced Differential Signal, 100Ω, RJ-45
 - Cable : Unshielded Twisted Category 5, 5e, 6 AWG24-4P
 - Internal Operation Frequency : 130MHz, -3dB
 - Internal Distortion : 60dB@5MHz
 - Differential Phase Error : 0.04 Degree NTSC, 150Ω
 - Operating Temperature Range : -40°C ~ +85°C
 - Internal Power Dissipation : Max 600mW
 - Humidity Range : 0% ~ 90%

MVUT-100

Video UTP Transmitter




Equipment Overview & Function

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

Specifications

- Case Part
 - Weight : 200g
 - Dimensions : 68(W) * 78(H) * 25(D) mm



[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech. All rights reserved
Lead the 21st century with technology and service ..

Asia
China
Singapore
Korea

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217