

MVUR-100

Video UTP Receiver



장비개요 및 성능

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

Description

- 본 장비는 Video UTP Receiver로서 Video신호 전송기인 Video Transmitter(MVUT-100)에서 UTP Cable로 전송된 신호를 Composite Video 신호로 출력하여주는 장치이다.

Features

- Video 출력은 NTSC/PAL을 지원하며 UTP Cable은 CATEGORY 5, 5E, 6을 사용할 수 있으며, 송신기와 수신기 접속은 Point-to-Point로 접속하여 사용하고, PAN/TILT 제어용 RS-485신호도 UTP Cable을 통하여 제어함으로써 추가 Cable 설치가 불필요하다.
- MVUR-100은 4Ch DIP 스위치를 이용하여 250m, 500m, 750m, 1000m 거리별로 간편하게 조정할 수 있으며, 세부 조정은 Gain 단자를 이용하여 깨끗한 화질을 구현 할 수 있다.

Panel Drawing



Specifications

- General Part
 - Input : Balanced Differential Signal, 100Ω, RJ-45
 - Output : 1 Vp-p Composite Video, 75Ω, NTSC/PAL, BNC Connector
 - AUX Input / Output Port : Control Data or Stereo Unbalanced Audio, WAGO Connector
 - Cable : Unshielded Twisted Category 5, 5e, 6 AWG24-4P
 - Internal Operation Frequency : 130MHz, -3dB
 - Internal Distortion : 60dB@5MHz
 - Differential Phase Error : 0.04 Degree NTSC, 150Ω
 - Operating Temperature Range : -40°C ~ +85°C
 - Internal Power Dissipation : Max 600mW
 - Humidity Range : 0% ~ 90%

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech. All rights reserved
Lead the 21st century with technology and service ..

**Asia
China
Singapore
Korea**

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217

MVUR-100

Video UTP Receiver



장비개요 및 성능

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

■ Specifications

- Case Part
 - Weight : 200g
 - Dimensions : 68(W) * 78(H) * 25(D) mm

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech. All rights reserved
Lead the 21st century with technology and service ..

Asia
China
Singapore
Korea

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217