

MDRU-3200

Data Receiver Unit



Equipment Overview & Function

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

Description

- This device enables to route one channel audio input signals to corresponding 32 output channels.

Features

- Remote Control terminal helps to route one channel audio input signals to corresponding 32 output channels.
- RS-422 is used for data transmission with speed of 4800 bps.
- Address / Baud can be set up as DIP Switcher.

Panel Drawing



Specifications

- General Part
 - Input Port : Audio Signal 1 ch
 - Output port : Audio Signal 32 ch
 - Control Part : CPU 8 bit MICRO PROCESSOR
 - Communication : RS-422 (DIP SW- ADDRESS)
 - Communication Speed : 8Bit, 1Stop Bit, None Parity, 4800Bps
- Case & Power Part
 - Power source : DC5V/24V, 2 PIN Wago Connector
 - Temperature : 0°C ~ 40°C
 - Power consumption : below 40Watt
 - Dimensions : 270(W) *35 (H) *157(D) mm

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

**Asia
China
Singapore
Korea**

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217