

MDTU-1600

Data Transmitter Unit



Equipment Overview & Function

Max Digital Tech Co., Ltd <http://www.maxdigital.co.kr>

Description

- This device enables to control 16 channels connected signals of the device and transmits them.

Features

- It has one port of remote control terminal.
- Receiving 1~16 terminals, Remote Control terminal helps to control data according to RS-422/RS-485 communication system.
- RS-422 is used for data transmission with speed of 4800 bps.

Panel Drawing



Specifications

- General Part
 - Input Port : 16 Relay
 - Remote control port : 1 RS-422 or 485 1Port
 - CPU : 8 bit MICRO PROCESSOR
 - Communication : RS-422/RS-485
 - Communication Speed : 8Bit, 1Stop Bit, None Parity, 4800bps
- Case & Power Part
 - Power source : 5V, 2 PIN Wago Connector
 - Temperature : 0°C ~ 40°C
 - Power consumption : below 20Watt
 - Dimensions : 215(W) *44.5(H) *130(D) mm

[www.maxdigital.co.kr]



Max Digital Tech Co.,Ltd

Copyright 2006 Max Digital Tech.All rights reserved
Lead the 21st century with technology and service ..

**Asia
China
Singapore
Korea**

+65 81335582
+86 021 54249750
+65 81335582
+82 2 2026 1200

Fax. +65 67828910
Fax. +86 021 54240199
Fax. +65 67828910
Fax. +82 2 2026 1217