



TYPE	0.5	1.0	2.0	4.0	6.0	8.0	13	16	19
TORQUE(kg·m)	0.55	1.1	2.2	4.5	7	7	14	17.5	20
CAPACITY(W, 20°C)	11	15	20	25	30	35	40	45	55
GAP	0.3	0.3	0.3	0.5	0.5	0.5	0.5	0.5	0.5
HUB dH7	12	15	20	25	30	30	30	40	40
KEY bE9 X h	4X13.8	5X17.3	5X22.3	7X28.3	7X33.3	7X33.3	7X33.3	10X43.3	10X43.3
A	63	80	100	125	137	180	180	200	216
B	68	85	106	133	146	190	190	213	229
E1	43	55	60	78	88	109	109	128	138
E2	7	8	8	10	10	11	11	12	12
G	38	45	55	64	75	88	88	90	104
H	28	30	34	38	40	60	60	60	60
I	1.5	2	3	4	4	4	4	6	6
K	24	26.5	30	33.5	34.5	49	49	49	49
L	57.3	65.8	77.3	94	104	139.5	139.5	144.5	152.5
M	20	25	30	40	45	55	55	60	65
N	33	40	47	52	62	74	74	75	92
R	3XM4	3XM4	4XM4	4XM4	4XM4	4XM5	4XM6	4XM6	4XM8
S1	5	7	9	9	11	11	13	13	13
S2	15	16	20	22	25	30	30	30	40
W X U	4X39.5	5X47	5X57	7X67	7X78	7X78	7X91	10X93	10X107

Example

