





SCA680 / 680A

- SCA680/680A are CE certified SCBA in its category and it is focused on the most critical functions and features so that user can have the maximized maneuverability and operational capability.
- SCA680/680A's quick-release mechanism on the waist belt and harness, it is simple and easy to maintain, and service, ensuring that the SCBA is always available to use.
- It provides wide range of air cylinder due to its condition of application.



Components

BASIC COMPONENTS			OPTIONAL COMPONENTS	
				
Face-piece	Air cylinder	Harness	SCBA Carrier	

Features (SCA680 ● SCA680A ▲)



FBO system ● ▲

- Allowing activation of SCBA without free flow.
- Second stage regulator activates pneumatic system by first breath.



Moving harness ▲

- Ergonomic backframe design that shift the weight from the shoulders to the hips promoting greater user acceptance.



Integrated regulator ▲

- First stage regulator integrated with alarm.
- Simplify design guarantee for low cost of ownership to maintain.

Specification

Data sheet	6.8liter	9.0liter
Service time	45 min	60 min
Weight	8.5kg(W/O Air)	10kg(W/O Air)
Cylinder	Material	Carbon Composite
	Water Vol.	Approx. 6.8liter
	Max. Air Capacity	2,040liter
	Weight	3.6Kg
	Service pressure(FP)	300bar
	Test pressure(TP)	500bar
	Standard	CE

Certification: CE(EN137:2006, EN136:1998), MED