

0.6/1kV 고무절연 캡타이어케이블(PNCT)

0.6/1kV EPR Rubber Insulated Flexible Cable

Applicable Standard: IEC 60502-1

선심수 No. of Cores	도체 Conductor		절연체두께 Insulation Thickness	시스두께 Sheath Thickness	완성외경 Overall Diameter	도체저항 (20℃) Conductor Resistance	시험전압 Test Voltage
	공칭단면적 Nominal Area	등급 Class					
C	mm ²	-	mm	mm	mm	Ω/km	kV
1	1.0	5	1.0	-	-	20.0	3.5
	1.5	5	1.0	1.6	7.9	13.7	3.5
	2.5	5	1.0	1.6	8.4	8.21	3.5
	4	5	1.0	1.7	9.1	5.09	3.5
	6	5	1.0	1.7	10.2	3.39	3.5
	10	5	1.0	1.8	11.6	1.95	3.5
	16	5	1.0	1.9	12.9	1.24	3.5
	25	5	1.2	2.0	14.9	0.795	3.5
	35	5	1.2	2.1	16.3	0.565	3.5
	50	5	1.4	2.2	18.6	0.393	3.5
	70	5	1.4	2.4	20.9	0.277	3.5
	95	5	1.6	2.5	23.5	0.210	3.5
	120	5	1.6	2.6	25.4	0.164	3.5
	150	5	1.8	2.8	28.1	0.132	3.5
	185	5	2.0	3.0	30.9	0.108	3.5
	240	5	2.2	3.2	34.6	0.0817	3.5
300	5	2.4	3.4	38.0	0.0654	3.5	
400	5	2.6	3.7	43.2	0.0495	3.5	
2	1.0	5	1.0	1.8	11.5	20.0	3.5
	1.5	5	1.0	1.9	12.3	13.7	3.5
	2.5	5	1.0	1.9	13.3	8.21	3.5
	4	5	1.0	2.0	14.5	5.09	3.5
	6	5	1.0	2.1	17.0	3.39	3.5
	10	5	1.0	2.3	19.8	1.95	3.5
	16	5	1.0	2.5	22.4	1.24	3.5
	25	5	1.2	2.7	26.4	0.795	3.5
	35	5	1.2	2.9	29.2	0.565	3.5
	80	5	1.4	3.1	33.8	0.393	3.5
	70	5	1.4	3.4	38.2	0.277	3.5
	95	5	1.6	3.7	43.6	0.210	3.5
	120	5	1.6	3.9	47.4	0.164	3.5
	150	5	1.8	4.2	52.6	0.132	3.5

•도체등급 : Class 5(Bunch or Member)