

IP IR Bullet Camera

Design



Specifications

Model	SJC44B92PIT
Image Sensor	1/3" 2.43M Panasonic CMOS image sensor
Lens	2.8~11mm TDN DC auto iris MP lens
Minimum Illumination	0.000 Lux (IR on)
Compression	H.264/MJPEG
Max Streaming Speed	Max 30fps @ 1920X1080
Scanning System	Progressive
Bit Rate Control	VBR/CBR (H.264, 32k~12Mbps)
Standard	ONVIF(Profile S) / PSIA(v1.0)
LAN Interface	10/100-base-T
Protocol	HTTP, RTP/RTSP, TCP/IP, FTP, Telnet, RARP, PPPoE, SNMP, PAP, CHAP, DHCP, NTP, SMTP client and etc
Viewer	IE6, Firefox, Safari, etc CMS, QuickTime
Remote Admin	Web based administration, setup, control, and upgrade
Advanced Service	E-mail / FTP / Alarm buffering Event notification
Dynamic IP	DDNS / uPnP support
Security	Multilevel password channel-wise privilege
Operating Temperature	-10℃ to 50℃
Operating Humidity	10% to 90% RH
Power Supply	PoE (IEEE802.3af)
Dimension/mm	Φ76 X 210(W) X 109(H)
Weight/g	920

Key Features

- 1/3" 2.43M Panasonic CMOS image sensor
- H.264/MJPEG, Dual Stream IP Camera
- Max. 30fps/Full HD (1920x1080)
- Remote access for Web Browser
- Network Bandwidth Control
- Event Alarm, e-mail, ftp Function
- RTP/RTSP(Multicast)
- Upgrade for Remote Access
- Support ONVIF & PSIA Standards
- 42 pcs of IR LEDs covering 40 meters
- 2.8~11mm TDN DC auto iris MP lens
- True Day & Night function with ICR mechanism
- 3-axis concealed bracket
- External Zoom & Focus Adjustable
- Weatherproof / IP-66 compliant
- PoE (IEEE802.3af)

Specification & Design are subject to change without prior notice

Dimensions

