

16-Ports/10-Ports PoE Ethernet Switch

16-Ports PoE 10/100/1000Mbps TP + 2-SFP Slots: SFC516HP

10-Ports PoE 10/100/1000Mbps TP: SFC510HP



SFC516HP/SFC510HP

SFC516HP

- 16-Ports PoE(802.af/at) 10/100/1000Mbps TP
- Full-duplex mode IEEE802.3x flow control
- 9216bytes jumbo frame packet
- 2-SFP Slots 1000Mbps

SFC510HP

- 10-Ports PoE 10/100/1000Mbps TP(802.3at 8-Ports)
- IEEE 802.3at PoE 30.8W 8-Ports(Max. 250W)
- IEEE 802.3af PoE 15.4W 8-Ports

Specifications

		SFC516HP	SFC510HP
Technology	- Standard	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX IEEE 802.3ab 1000Base-T IEEE 802.3 af, IEEE 802.3 at	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX IEEE 802.3ab 1000Base-T IEEE 802.3 af, IEEE 802.3 at
Interface	- RJ45 Ports	16-Ports 10/100/1000Mbps TP Auto-Negotiation, Auto MDI-X TP/STP Cat. 3,4,5 Cable EIA/TIA-568 100-ohm(100m)	10/100/1000Base-T(X) Auto-negotiation, Auto MDI-X UTP/STP Cat. 3,4,5 Cable EIA/TIA-568 100-ohm(100m)
	- SFP Slots	2-SFP Slots, 1000Mbps-SX/LX SFP	
	- LED Indicators	Power, FD, Link/Act, Speed, PoE	
Performance	- PoE (Power over Ethernet)	Max. 260 watt 8-Ports : 30.8watt 16-Ports : 15.4watt	Max. 250watt 1~8Ports : 15.4watt, 30.8watt 9,10-Ports Uplink
Environmental	- Temperature	Operation: 0°C ~ 40°C, Store: -10°C ~ 70°C	Operation: 0°C ~ 60°C, Store: -20°C ~ 80°C
	- Humidity	5% ~ 95% (Non-condensing)	
Power Supply	- Input Voltage	100~240VAC, 50/60Hz	
Mechanical	- Dimensions	440mm(W) x 205mm(D) x 44mm(H)	280mm(W) x 185mm(D) x 44mm(H)

Ordering Information

Model Name	Description
SFC516HP	16-Ports PoE 10/100/1000Mbps TP + 2-SFP Slots
SFC510HP	10-Ports PoE 10/100/1000Mbps TP(802.3at 8-Ports)
SFP-SX	SFP(1.25Gbps) Module, Multi-mode, 220/550m, 850nm, LC Type
SFP-LX	SFP(1.25Gbps) Module, Single-mode, 20Km, 1310nm, LC Type