

PoE Extender

1-Port 10/100Mbps PoE Extender



SFC502H/SFC502

- Transmission Distance : Max. 100m
- Daisy Chain connections: Max. 300m
- IEEE 802.3af/at(SFC502H)
- Operates without additional input power source
- Industrial grade operation temperature(SFC502H)

Specifications

		SFC502H	SFC502
Technology	- Standard	IEEE 802.3af Power over Ethernet IEEE 802.3at Power over Ethernet IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-T Fast Ethernet	IEEE 802.3af Power over Ethernet IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-T Fast Ethernet
Interface	- RJ45 Ports	10/100Mbps	
Performance	- PoE (Power over Ethernet)	Max. 25Watt Number of PD@25Watt Number of PSE@30Watt	Max. 15Watt Number of PD@12.95Watt Number of PSE@15.40Watt
	- PoE Input In	1/2(-), 3/6(+) and 7/8(-), 4/5(+)	
	- PoE Input Out	1/2(-), 3/6(+) Output Power : up to 22W	1/2(-), 3/6(+) Output Power : up to 15.4W
Environmental	- Temperature	Operation: -40°C ~ 55°C	Operation: 0°C ~ 50°C
	- Humidity	10% ~ 90% (Non-condensing)	
Mechanical	- Dimensions	60mm(W) x 145mm(D) x 40mm(H)	48.4mm(W) x 88.2mm(D) x 25mm(H)

Ordering Information

Model Name	Description
SFC502H	1-Port 10/100Mbps, 25Watt, PoE Extender
SFC502	1-Port 10/100Mbps, 15Watt, PoE Extender