

Industrial 2.5Gigabit Ethernet Switch Chassis

SFC8000G-1U: 19" Rack Type, 1U Size, 2-Slots, bypass option

SFC8000G-4U: 19" Rack Type, 4U Size, 8-Slots



SFC8000G-1U/SFC8000G-4U

- Bypass(SFC8000G-1U option)
- SFC8000G-1U: 19" Rack Type, 1U Size, Bypass option
- SFC8000G-4U: 19" Rack Type, 4U Size, 8-Slots
- Power redundant

Specifications

Interface	- Slots	SFC8000G Switch Module SFC-Bypass Module
	- LED Indicators	Per unit: Power, Power Input1, Power Input2, Fault/Alarm, Ring Master 1000Mbps TP Port: Speed(1000Mbps Yellow), Link/Activity(Green), Mini-GBIC: Link/Activity(Green)
Environmental	- Temperature	Operation: -40°C ~ 80°C, Store: -40°C ~ 85°C
	- Humidity	5% ~ 95% (Non-condensing)
Power Supply	- Input Voltage	100~ 240VAC, 50/60Hz
Mechanical	- Dimensions	SFC8000G-4U: 443.5mm(W) × 256mm(D) × 174.4mm(H) SFC8000G-1U: 417mm(W) × 225.6mm(D) × 44.5mm(H)

Ordering Information

Model Name	Description
SFC8000G-1U	SFC8000G, 19" Rack Type, 1U 2-Slots, bypass option, Power redundant
SFC8000G-4U	SFC8000G, 19" Rack Type, 4U 8-Slots, Power redundant