

HDMI IP(TP/Fiber) Extender

4K HDMI over TCP/IP Network, TP/Fiber Combo



SFC1200-HDFT/SFC1200-HDF/SFC1200-HDT

SFC1200-HDFT

- 4K HDMI over TCP/IP
- 1-Port 1000Mbps TP, Fiber Combo
- 1-SFP Slot 1000Mbps
- Multicasting(1:1, 1:N)

SFC1200-HDF

- Full HD(1080p) over TCP/IP
- 1-Port 100Mbps Fiber
- Multicasting(1:1, 1:N)

SFC1200-HDT

- Full HD(1080p) over TCP/IP
- Real-time Latency 30~50ms
- 1-Port 100Mbps TP
- Multicasting(1:1, 1:N)

Specifications

		SFC1200-HDFT	SFC1200-HDF	SFC1200-HDT
Interface	- HDMI	HDMI 1.4	HDMI 1.3a	HDMI 1.3a
	- Ethernet	1-Port 10/100/1000Mbps	1-Port 10/100Mbps	1-Port 10/100Mbps
	- Fiber Ports	1000Mbps SFP Slot	100Mbps WDM Fiber	Not Support
	- Resolution	DTV/HDTV: 480i, 576i, 480p, 576p, 720p, 1080i, 1080p, 4K		
Environmental	- Temperature	Operation: 0°C ~ 60°C		
	- Humidity	5% ~ 90% (Non-condensing)		
Power Supply	- Input Voltage	DC 12V, 1.5A	DC 5V, 2A	DC 5V, 1A
Mechanical	- Dimensions	97(W) x 135(D) x 26(H)	97(W) x 135(D) x 26(H)	51(W) x 85(D) x 20(H)

Ordering Information

Model Name	Description
SFC1200-HDFT	4K HDMI over TCP/IP Network, TP/Fiber Combo
SFC1200-HDF	Full HD(1080p) HDMI over TCP/IP Network
SFC1200-HDT	Real-time Full HD(1080p) HDMI over TCP/IP Network