# BEACON



BEACON 1 : AIRPORT BEACON BEACON 2 : HELIPORT BEACON

### Compliance with standards

ICAO : Annex14 Para 5.3.3 FAA : AC 150/5345-12, L-801A,H K S : KS W 5061(Korean Standard)

The Airport Rotating Beacon identifies the location of an airport from a distance and is designed for use at commercial and regional airports and heliports.


The rotating beacon consists of two main assemblies; an upper part with a rotating shaft equipped with three (heliports) or four (airport) high intensity lamp units and a base part with motor, gear assembly, control unit and electrical connections. The BEACON is switched on and off from the Airfield Ground Lighting remote control console.

### **Features**

- Meets FAA specification AC 150/5345-12 L-801
- Operating temperature: 30°C to + 55°C
- High reliability
- · Housing in aluminium alloy coated in aviation orange
- Lamp heads in aluminium alloy
- Three lamp heads for heliport
- Four lamp heads for Airport; two lamps are used as back-up and will automatically be energized in case of failure of one of the on duty lamps
- 1000 W, PAR 64 lamps
- Power supply: 220 / 240 V 50 or 60 Hz
- Optional obstruction light



## **BEACON**





Technical Data			
Lamps	PAR 64 1000W 120V		
Flashing Rate	Airport BEACON: 24 ~ 30 F/min		
	Heliport BEACON: 30 ~ 45 F/min		
Input Voltage	Single Phase 220V/240V 50/60Hz		
	(120V upon request)		
Power Consumption	Airport BEACON: 2500W max		
	Heliport BEACON: 3500W max		
Drive Motor	1/8HP		
Temperature Range	-30°C to +55°C in operation		

### Ordering Code



Light Color 01: White/Green(Airport) 02: White/Green/Yellow(Heliport)

Description			
Model Name	Item	Specification	
BEACON1	Airport Beacon	1,000W * 4	
BEACON2	Heliport Beacon	1,000W * 3	

Spare Parts			
Description	Specification	Ordering code	
Lamp	120V 1,000W(PAR64)	111-450A	
Filter	Green ø210*3T	143-054A	
Filter	Yellow #210*3T	143-055A	



### **Head Office**

738-2, Kwanyang-Dong, Dongan-Ku, Anyang-City, Kyunggi-Do, Korea Tel: 82-31-422-0021 Fax: 82-31-424-6044